

Hydraulic Jack Oil – ISO22 Biobased Hydraulic Oil

Part No: 10573, 10574, 10575

DESCRIPTION

Hydraulic Jack Oil is a biobased, biodegradable hydraulic oil formulated with the best optimized USA-grown natural seed oils that surpass the lubricity of most conventional oils. It protects against wear and has a high flash point for safety.

APPLICATIONS

- ▶ Recommended for industrial and home hydraulic jacks
- ▶ Not designed for use in hydraulic brake systems

BENEFITS

- ► Reduces wear through superior thin film protection
- ▶ Protects all ferrous metal components from rust and corrosion
- ► Superior performance for brass or bronze-on-steel contacts
- ► Maintains stable viscosity through wide operating temperature range
- ► Good seal compatibility
- ▶ Mostly benign when released into the environment
- ► Has superior flash and fire points for increased safety
- ► EPA's Environmental Preferable Purchasing (EPP) criteria
- ▶ Manufactured from renewable USA-grown crop based oils

TYPICAL PROPERTIES	Property	Method	Value
	ISO Viscosity Grade		22
	Base Oil Viscosity at 40°C (cSt)	ASTM D-445	23
	Base Oil Viscosity at 100°C (cSt)	ASTM D-445	5.9
	Viscosity Index	ASTM D-2270	221
	Flash Point °C (°F)	ASTM D-92	161 (322)
	Pour Point °C (°F)	ASTM D-97	-18 (Ò)
	Rust & Corrosion	ASTM D-130	1A; Shiny
	Base Oil Biodegradability	OECD	Pass
	Base Oil Aquatic Toxicity	Daphnia Magna	Non-toxic

PACKAGING

Quarts, Gallons, 5-Gallon Plastic Pail

DATA PROVIDED IN THIS BULLETIN IS TO BE CONSIDERED AS REPRESENTATIVE OF CURRENT PRODUCTION GENERALLY AND NOT AS SPECIFICATIONS. WHILE ALL THE DATA PRESENTED IN THIS BULLETIN IS BELIEVED TO BE RELIABLE, AND BECAUSE CONDITIONS OF USE ARE BEYOND OUR CONTROL, LUBRIMATIC MAKES NO REPRESENTATIONS, GUARANTEES OR WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, OR AS TO THE CORRECTNESS OR SUFFICIENCY OF DATA HEREIN PRESENTED. EACH USER SHOULD CONDUCT A SUFFICIENT INVESTIGATION TO ESTABLISH THE FITNESS OF ANY PRODUCT FOR ITS INTENDED PURPOSE. NO AGENT, REPRESENTATIVE, OR EMPLOYEE OF THIS COMPANY IS AUTHORIZED TO VARY ANY OF THE TERMS OF THIS NOTICE. TO CONTINUE TO PROVIDE SUPERIOR QUALITY, LUBRIMATIC RESERVES THE RIGHT TO CHANGE THE COMPOSITION OF ITS PRODUCTS WITHOUT NOTICE.

Plews/Edelmann ● 1550 Franklin Grove Road ● Dixon, IL 61021 ● Telephone 800-770-4639 ● Fax 815-288-3388 ● www.ultra-lube.com