Commercial and Industrial Water Treatment Programs Since 1927

Product Information:

Trade Name (as labeled):	SKASOL MB-8
Manufacturer's Name	Skasol Incorporated
Address (complete mailing address):	1696 West Grand Avenue
	Oakland, California 94607-1607
24 Hour Emergency Telephone	(800) 424-9300
Information Telephone	(510) 839-1000
Date prepared or revised	January 1, 1999
Name of preparer	Karlyn Gibson

Hazardous Ingredients:

Chemical Name	CAS Number	Percent	Limits in Air ACGIH TLV	(give units) OSHA PEL	Other (specify)
Tributyltin Oxide	56-35-9	<5%	0.1mg/m ³		as Tin (Sn)
Alkyl Dimethyl Benzyl Ammonium Chloride	68391-01-5	<10%	not established		
Alkyl Dimethyl Ethyl Benzyl Ammonium Chloride	68956-79-6	<10%	not established		

Physical Properties:

Vapor Density	not available	Melting Point or Range	not applicable	
Specific Gravity	1.05	Boiling Point or Range, °F	218	
Solubility in Water	complete	Evaporation Rate	not available	
Vapor pressure not available				
Appearance and Odor		Blue liquid, detergent odor		
How to detect this substance		Irritation of respiratory tract will occ	cur if inhaled	

Fire and Explosion:

Flash point, °F (give method)	none
Auto ignition temperature, °F	none

Flammable limits in air, volume %	none	lower (LEL)	upper (UEL)	

Fire extinguishing materials:

Water	X	Foam	Х	CO ₂	X	Dry Chemical	Χ	Other	
Special fire	fighting proc	edures:	Wear full protective clothing and respiratory protection						
Unusual fire	and explosi	on hazards:	None	None					

Health Hazard Information:

Symptoms of overexposure for each potential route of exposure

Symptoms of Overexposur	e for each potential route of exposure.
Inhaled:	Mist or liquid will cause major irritation of the respiratory tract. Large amounts will cause burning from
	sensations in nose and throat. Possible bleeding from nose may occur, coupled with coughing, chest
	discomfort and tightness, difficulty in breathing and headache.
Contact with skin or eyes:	Causes severe damage to eyes. Skin is more resistant, but prolonged exposure can cause irritation.
Absorbed through skin:	May be absorbed through skin if contact is prolonged.
Swallowed: Will cause burning damage to mouth, esophagus, stomach, etc. Get immediate medical attention.	
HEALTH HAZARD	FIRE HAZARD

4. Deadly
3. Extreme Hazard
2. Hazardous
1. Slightly Hazardous
0. Normal Material

FIRC. FIAZARU

4. Below 73 degree F (Boiling pt. below 100 degree F)

3. Below 73 degree F (Boiling pt. at/above 100 degree F
and/or at/above 73 degree F not exceeding 100 degree F)

2. Above 100 degree F not exceeding 200 degree F

1. Above 100 degree F

0. Will not burn

SPECIFIC HAZARD REACTIVITY

4. Oxidizer
3. Acid
2. Alkali
1. Corrosive
0. Use no water

4. May detonate
3. Shock and heat may detonate
2. Violent chemical change
1. Unstable if heated
0. Stable

Health Hazard	2
Fire Hazard	0
Reactivity Hazard	0
Specific Hazard	

Commercial and Industrial Water Treatment Programs Since 1927

Health Hazard Information (continued):

Heath effects or risks from exposure:

Acute	Will cause irritation to skin, respiratory and gastrointestinal tracts. Severe damage can occur.
Chronic	Same as acute only less severe.

First Aid Emergency Procedures:

Eye Contact	Immediately flush with plenty of water, raising eyelids often to help irrigation and continue for at least 15 minutes. Get medical assistance.
Skin Contact	Flush with plenty of water. Remove contaminated clothing. If skin is sticky, acidity is still present. Continue flushing until stickiness is gone.
Inhaled	Remove to fresh air. If not breathing give artificial respiration (preferably mouth to mouth). Call a physician or poison control center.
Swallowed	If conscious drink large quantities of water, milk or sodium bicarbonate. Do not induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.

Suspected cancer agent?

Х	No: this product's ingredients are	not found in the lists below.	
	Federal OSHA	National Toxicology Program	International Assoc. For Research On Cancer
Medical	Conditions Aggravated By Exposure	Dermititis, fibrotic lung	disease.

Reactivity Data:

Stability:

Х	Stable	Ur	nstable		
Conditions to avoid:		Do not mix with strong acids, bases, anionic surfactants.			
Incompatibility (materials to avoid): Strong bases, acids, anionic surfac			surfactants.		
Hazardous decomposition products: Tin Oxide compounds.					
Hazardous	polymerization:		May occur	Х	will not occur
Conditions to avoid:			Not known		

Spill, Leak and Disposal Procedures:

Spill response procedures:	Dike area to contain the spill. Small spills may be flushed and diluted with lots of water and washed to
370 37 46	a sewer connected to a waste treatment plant.
Preparing wastes for disposal:	Larger spills should be contained and neutralized with dilute base before washing with plenty of water to a sewer connected to a waste treatment plant. Any DOT container is suitable for temporarily holding
	neutralized waste.

Special Handling Information:

Ventilation and Engineering Controls:	Local exhaust ventilation should be sufficient to minimize employee exposure to mist below OSHA PEL
Respiratory Protection:	When conditions require it, use a respirator approved by NIOSH/MSHA with a dust/mist filter. Respiratory protection programs must meet or exceed the requirements of Title 29 CFR 1910.134
Eye Protection:	Close fitting chemical safety goggles with a face shield if needed.
Gloves:	Nitrile, neoprene or natural rubber.
Other Clothing and equipment	Rubber boots with safety toes, rubber aprons, plastic hard hats should be used when necessary to prevent skin contact.
Work practices, hygienic practices:	Protective clothing and use of equipment must be in accordance with Title 29 CFR Sections 1910.132 and 1910.133
Other Handling and Storage Needs:	Provide emergency eye wash stations and emergency shower facilities near use and handling areas.
Measures during Maintenance:	Chemical feed pumps should be routinely washed out with water. Plastic tubing and fittings should be frequently inspected for leaks and clogs. As with all automatic equipment, be certain that the power is disconnected before performing any adjustments or repairs. Use all above precautions.