



Material Safety Data Sheet

The information presented in these forms is believed to be correct and sufficient to meet the requirements of OSHA Hazard Communication standard (29 CFR 1910.1200) concerning worker's right to know. In order for the information contained in the MSDS to be most helpful we recommend that these forms be made available to all those who handle or may otherwise be exposed to the product.

This MSDS covers the following Aervoe aerosol product.

PRODUCT NAME: 875 Label Adhesive

HMIS RATING: Health 1, Flammability 4, Reactivity 0

NFPA RATING: Toxicity 1, Flammability 4, Reactivity 0

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: Aervoe Industries Inc.

ADDRESS: 1198 Mark Circle, Gardnerville, NV 89410

INFORMATION PHONE: 775-782-0100

EMERGENCY PHONE: 1-800-424-9300

DATE REVISED: 02-25-04

REASON REVISED: Revised

SECTION II - HAZARDOUS INGREDIENTS / SARA III INFORMATION OCCUPATIONAL EXPOSURE LIMITS

HAZARDOUS COMPONENTS	WEIGHT PERCENT	OSHA PEL	ACGIH TLV	OTHER
2-Propanone (CAS 67-64-1)		1000 ppm	500 ppm	750 ppm STEL
*Hexane (CAS 110-54-3)		50 ppm	50 ppm	
*Cyclohexane (CAS 110-82-7)		300 ppm	300 ppm	
Liquefied Petroleum Gas (CAS 68476-86-8)		Unknown	1000 ppm	

*Indicates ingredients that are subject to the reporting requirements of Section 313 of EPCRA and 40 CFR 372

NOTE: N / AP = Not Applicable N / AV = Not Available

SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

Physical State: Mixture packaged in pressurized aerosol spray can. **Specific Gravity:** 0.770 - 0.800 g/mL
Appearance and Odor: White non-transparent liquid with a solvent odor. **Solubility in Water:** Insoluble.
pH: Not applicable. **Evaporation Rate (BuAc=1):** >1.00 **Volatile Organic Content (CARB):** 64.895% **Boiling Point:** >100°F

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

Extinguisher Media: Foam, Dry Chemical (B-C), CO2 **Flash Point(Concentrate):** <0°F(-17.78°C) **Flammability:** *EXTREMELY FLAMMABLE*
UNUSUAL HAZARDS: Do not expose to temperature exceeding 120°F as containers may vent, rupture or burst.
SPECIAL FIRE FIGHTING PROCEDURES: Keep containers cool using water spray. Use proper equipment to protect personnel from bursting containers.

SECTION V - REACTIVITY DATA

STABILITY: Product is stable. **CONDITIONS TO AVOID:** Do not use or store near fire, sparks, or flame.
HAZARDOUS POLYMERIZATION: Will not occur. **INCOMPATIBILITIES:** Avoid contact with acids, strong oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO2, various hydrocarbons.

SECTION VI - HEALTH HAZARD DATA

Inhalation: High concentrations of vapors may irritate nose and throat and cause symptoms of intoxication such as dizziness, nausea, headache, or indigestion.
Eye Contact: Direct spray or vapors will cause irritation. Symptoms include stinging, tearing, redness, and swelling of the eyes.
Skin Contact: Product may cause mild irritation. Prolonged or repeated contact may dry the skin. Symptoms include redness, burning, drying and cracking of skin, and skin burns.
Ingestion: Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This can result in lung inflammation and other lung injury.
PRIMARY ROUTES OF EXPOSURE: Inhalation, eye/skin contact.
CONDITIONS AGGRAVATED BY EXPOSURE: None known.
ANY INGRED. LISTED CARCINOGEN: OSHA: Not listed. IARC: Not listed. NTP: Not listed.
EMERGENCY AND FIRST AID PROCEDURES:
Inhalation: Remove victim to fresh air. Apply artificial respiration if needed. Get medical attention.
Eye Contact: Immediately flush eyes with water for at least 15 minutes. Get medical attention if irritation persists.
Skin Contact: Remove contaminated clothing and wash skin with soap and water. Get medical attention if irritation persists.
Ingestion: DO NOT INDUCE VOMITING unless directed by a physician or poison control center. Get medical attention immediately.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

PROCEDURES FOR CLEANING UP LEAKS AND SPILLS: Absorb spill with inert material then place in a chemical waste container. Dispose of spill material in accordance with regulations.
HANDLING: Use with adequate ventilation. Make sure containers are properly grounded before use or transfer of material. Deliberately concentrating and inhaling the contents of this container may be harmful and fatal. Keep out of reach of children. Read label precautions carefully and follow directions to avoid injury.
STORAGE: Do not use or store near fire, sparks, or flame. Do not store at temperatures above 120°F. Keep out of reach of children.
DISPOSAL: Dispose of waste material in accordance with state, local, and federal regulations.

SECTION VIII - CONTROL MEASURES

ENGINEERING CONTROLS: Maintain adequate ventilation.
PERSONAL PROTECTIVE EQUIPMENT: Use respirator only as a last resort to control exposure when engineering controls are not feasible. Wear chemical-resistant GLOVES if repeated skin contact occurs or causes irritation. Wear SAFETY GLASSES or GOGGLES to prevent eye contact.

SECTION IX - DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE SO. NOTHING CONTAINED HEREIN CONSTITUTES A SPECIFICATION NOR IS IT INTENDED TO WARRANT SUITABILITY FOR THE INTENDED USE.