#### MATERIAL SAFETY DATA SHEET FOR PROSTAR® WATER BASED ANTI-SPATTER AEROSOL PRS50214

#### **SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

PRODUCT NAME : PROSTAR® ANTI-SPATTER

PRODUCT IDENTIFIER : ANTI-SPATTER PRODUCT USE : ANTI-SPATTER ITEM CODE(S) : PRS50214 UPC BAR CODE(S) : 699913-119154

ADDRESS : PRAXAIR DISTRIBUTION INC

DANBURY, CT 06810-5113

PREPARED BY : KEMPER SYSTEM / QUALITY MANAGER

TELEPHONE : (905) 624-5463

EMERGENCY TELEPHONE : (613) 996-6666 (CANUTEC – Call collect)

PREPARATION DATE : JULY 01, 2012 OSHA REGULATORY STATUS : REGULATED

WHMIS CLASSIFICATION : A, B5

NOTE : THIS ITEM REPLACES PRS50101. IF YOU HAVE PRS50101 PRODUCT

REQUEST AND USE THE MSDS FOR ITEM PRS50101.

# **SECTION 2. COMPOSITION / INFORMATION ON INGREDIENTS**

HAZARDOUS INGREDIENTS	CAS	OSHA PEL		ACGIH TLV		LD50 SPECIES/ROUTE	LC50 SPECIES/ROUTE	%WT
OXIBISMETHANE	115-10-6	N/E		N/E		N/E	184 mg/l /4 hr, rat	10-30%

#### **SECTION 3. HAZARDS IDENTIFICATION**

## **EMERGENCY OVERVIEW**

CONTENTS UNDER PRESSURE. STORE BELOW 120°F (49°C), OUT OF SUNLIGHT AND AWAY FROM HEAT SOURCES. DO NOT PUNCTURE OR INCINERATE. AVOID CONTACT WITH SKIN AND EYES. VAPOR HARMFUL. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

EYE: Liquid or vapors may cause redness, burning, tearing, swelling and/or pain.

SKIN: Frequent or prolonged contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INGESTION: Due to being an aerosol, product does not lend itself to ingestion. Should ingestion occur,

it may cause irritation to membranes of the mouth, throat and gastrointestinal tract, resulting in vomiting and/or cramps.

INHALATION: Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, or confusion.

EFFECTS OF ACUTE EXPOSURE: N/Av EFFECTS OF CHRONIC EXPOSURE: N/ Av OTHER IMPORTANT HAZARDS: N/Av

SUGGESTED HMIS RATING: HEALTH | 1 | FLAMMABILITY | 1 | REACTIVITY | 0 | PERSONAL PROTECTION | A |

## **SECTION 4. FIRST AID MEASURES**

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.

INGESTION: Unlikely due to being in aerosol form. Should actual ingestion occur, do not induce vomiting! Drink a glass of water or milk to dilute. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. EYE CONTACT: Immediately flush with plenty of clear water for at least 15 minutes. Make sure to flush under the eyelids. Consult a physician for definitive treatment.

SKIN CONTACT: Remove with soap and water. Continue flushing with water for several minutes. Use skin cream to counter resulting dryness. Consult a physician if irritation continues or if large skin area is affected.

EFFECTIVE: JULY 01, 2012 PAGE 1 OF 4

#### **SECTION 5. FIRE FIGHTING MEASURES**

CONDITIONS OF FLAMMABILITY: Heat, sparks, flame, red hot metal.

MEANS OF EXTINCTION: For warehouse and storage conditions, use NFPA Class B extinguishers (CO<sub>2</sub>, dry chemical or universal aqueous film forming foam).

SPECIAL FIRE FIGHTING PROCEDURES: Use water spray to cool fire exposed aerosol containers for containers can rupture violently from heat developed pressure.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Contents extremely flammable and under pressure. In addition, when liquid or vapor comes into contact with flames or red hot metal, products of combustion will be created. Firemen should wear self-contained breathing apparatus.

FLASH POINT / DETERMINATION: Propellant < 0°F (<-18°C)

UPPER FLAMMABLE LIMIT: 9.5% LOWER FLAMMABLE LIMIT: 1.8% AUTO-IGNITION TEMPERATURE: N/Av

HAZARDOUS COMBUSTION PRODUCTS: N/Av

EXPLOSION DATA - SENSITIVITY TO MECHANICAL IMPACT: N/AV EXPLOSION DATA - SENSITIVITY TO STATIC DISCHARGE: N/AV

## **SECTION 6. ACCIDENTAL RELEASE MEASURES**

LEAK / SPILL RESPONSE: Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content should be contained as any other solvent spill. Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove all sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.

SPECIAL INSTRUCTIONS: Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal considerations.

#### **SECTION 7. HANDLING AND STORAGE**

HANDLING PROCEDURES / EQUIPMENT: Avoid prolonged or repeated skin contact. Avoid breathing vapors.

STORAGE REQUIREMENTS: Store in area below 120°F (49°C). Do not incinerate (burn) containers. Assure can is in a secure place to prevent knocking over and accidental rupture. Always replace over cap when not in use. For store of pallet quantities, compliance with ANSI/NFPA 30B is recommended.

## **SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

# PERSONAL PROTECTIVE EQUIPMENT





EYE PROTECTION: Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact could occur, chemical splash proof goggles are recommended.

SKIN PROTECTION: For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing such as Sol-Vex® gloves or other clothing impervious to the ingredient listed in Section 2.

ENGINEERING CONTROLS: General ventilation (typically 10 air changes for hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system, may be needed to control air contamination below that of the lowest TLV/PEL rated ingredient from Section 2.

EXPOSURE GUIDELINE LEVELS: Since this product is a mixture, an OSHA or ACGIH exposure value is not available. In determination of any exposure procedures, protection or testing use the lowest rated ingredient in Section 2.

EFFECTIVE: JULY 01, 2012 PAGE 2 OF 4

## **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

**Boiling Point** > 212 F (100 C) Flash Point, Liquid Content > 212 F (100 C) **Explosive Limits** 3.30% to 18.00% **Flammability** Flammable propellant **Molecular Weight** Not Available

**Vapor Pressure** 60 psig **Vapor Density** 9.70 g/cc Maximum **Physical State** Liquid Under Pressure

**Viscosity** Not Available **Percent Volatile** 78% Wt (79% Vol) Max

20% Wt (28 % Vol) Max **Percent VOC Odor Threshold** Not Available Lard-like odor Odor

**Appearance** 

clear to cream colored liquid

**Melting/Freezing Point** > 28 F (-2 C)Flash Point, Propellant -42 F (-41.1 C) 662 F (350 C) **Auto ignition Temperature** Specific Gravity (H<sub>2</sub>O = 1) 0.897 g/cc Weight 7.482 lbs/gal рΗ Not Available **Evaporation Rate** Not Available **Partition Coefficient** Not Available **Refractive Index** Not Available

**VOC Content** 1.496 lbs/gal (179.306 g/l)

**HAP Content** None **MIR Value** 0.186 g O<sub>3</sub>/g **Water Solubility** Not Available Not Available **Decomposition Temperature** 

## **SECTION 10. STABILITY AND REACTIVITY**

STABILITY: Stable.

CONDITIONS TO AVOID: Heat, sparks, flame, red hot metal.

MATERIALS TO AVOID (INCOMPATIBILITIES): Strong oxidizing materials.

CONDITIONS OF REACTIVITY: N/Av

HAZARDOUS DECOMPOSITION BYPRODUCTS: Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

# **SECTION 11.TOXICOLOGICAL INFORMATION**

LD50: N/Av LC50: N/Av

ROUTES OF ENTRY: INHALATION[Y] EYE CONTACT[Y] SKIN CONTACT[Y] SKIN ABSORPTION[Y] INGESTION[N] EXPOSURE LIMITS: Since this product is a mixture, an OSHA or ACGIH exposure value is not available. In determination of any exposure procedures, protection or testing use the lowest rated ingredient in Section 2.

IRRITANCY OF PRODUCT: N/Av

SENSITIZATION TO PRODUCT / MEDICAL CONDITIONS AGGRAVATED: N/Av

CARCINOGENICITY: None of the ingredients in this product are listed with IARC, NTP or OSHA as being carcinogenic.

TERATOGENICITY / MUTAGENICITY / REPRODUCTIVE TOXICITY: N/Av

TOXICOLOGICAL DATA: N/Av

## **SECTION 12. ECOLOGICAL INFORMATION**

ENVIRONMENTAL EFFECTS: This product has not been tested for environmental effects.

IMPORTANT ENVIRONMENTAL CHARACTERISTICS: N/Av

AQUATIC TOXICITY: N/Av

## **SECTION 13. DISPOSAL CONSIDERATIONS**

An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

PAGE 3 OF 4 EFFECTIVE: JULY 01, 2012

SPECIAL SHIPPING INFORMATION : N/Av

**DOT HM-181 SHIPPING INFORMATION** 

PROPER SHIPPING NAME : Consumer Commodity

HAZARD CLASS OR DIVISION : ORM-D UN NUMBER : 1950 PACKAGING GROUP : none LABEL(S) REQUIRED : none



LIMITED

QUANTITY

TDG SHIPPING INFORMATION

TDG SHIPPING NAME : Aerosols, Flammable Limited Quantity

TDG CLASSIFICATION : 2.1
UN NUMBER : 1950
PACKING GROUP : none
LABEL(S) REQUIRED : none
NAERG : 126

EMERGENCY TELEPHONE NUMBER : (613) 996-6666

INTERNATIONAL TRANSPORT INFORMATION

PROPER SHIPPING NAME : Consumer Commodity

CLASS OR DIVISION : 9 SUBSIDIARY RISK : none

HAZARDOUS LABEL(S) : Miscellaneous

PACKAGING GROUP : none UN OR ID NUMBER : ID8000



## **SECTION 15. REGULATORY INFORMATION**

TOXIC SUBSTANCES CONTROL ACT (TSCA): The product on this MSDS, or all of its components, is listed under TSCA. SARA TITLE III, SECTION 313: The following ingredients are subject to the reporting requirements of section 313 of Title III of the Superfund and Reauthorization Act of 1986 and 40 CFR Part 372: None

CLEAN AIR ACT (CAA): The following ingredients appear on the List of Hazardous Air Pollutants (HAP – 42 USC 7412, Title I, Part A, p112): None

CLEAN WATER ACT (CWA): The following ingredients appear on the CWA List of Hazardous Substances (40 CFR 116.4): None CALIFORNIA PROPOSITION 65: The following ingredients appear on the Proposition 65 list(s): None

CANADIAN WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM (WHMIS): This MSDS has been prepared according to the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

DOMESTIC SUBSTANCES LIST (DSL): The product on this MSDS, or all of its components, is included in the DSL.

#### **SECTION 16. OTHER INFORMATION**

N/E Not Established
N/Av Not Available
N/Ap Not Applicable
IARC International Ager

IARC International Agency for Research on Cancer

ACGIH American Conference of Governmental Industrial Hygienists
NIOSH National Institute for Occupational Health and Safety
TLV-TWA Threshold Limit Values, Time Weighted Average

NAERG North American Emergency Response Guidebook WHMIS Workplace Hazardous Materials Information System

This MSDS format meets ANSI Z400.1-1998, OSHA 1910.1200 and WHMIS requirements. Praxair Distribution Inc provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Product use and conditions of use are beyond the control of Praxair Distribution Inc. Warranty of materials is limited to test results of product performance as detailed in certificates of compliance. Interpretation of test results is the responsibility of end-user. No other warranties, expressed or implied, are made. Incorporating new format, general update from 01/09/2007.

EFFECTIVE: JULY 01, 2012 PAGE 4 OF 4