

211/9640
A02/235

MATERIAL SAFETY DATA SHEET

DAP CANADA INC.
475 FINCHdene SQUARE
UNIT 5
SCARBOROUGH, ONTARIO MIX 187

MSDS NO: DAP / 30807
INTERNAL ID: 30807
DAP WELDWOOD MULT-PURPOSE
FLOOR ADHESIVE
REVISION: 6
DATE: JANUARY 17, 1995

NATIONAL PAINT AND COATINGS ASSOCIATION	HEALTH HAZARD	1 - SLIGHT
HAZARDOUS MATERIAL IDENTIFICATION SYSTEM	FLAMMABILITY HAZARD	1 - SLIGHT
	REACTIVITY HAZARD	0 - MINIMAL
	PERSONAL PROTECTION	B - GLASSES, GLOVES

SECTION I. MATERIAL IDENTIFICATION

TRADE/MATERIAL NAME: DAP WELDWOOD MULT-PURPOSE FLOOR ADHESIVE

DESCRIPTION: ADHESIVE

CAS: MIXTURE

PREVIOUS MSDS REVISION DATE: JUNE 13, 1994

INFORMATION FOR DOMESTIC GROUND TRANSPORT:
SHIP NAME (49 CFR 172.101): NONE
D.O.T. ID NO. (49 CFR 172.11): NONE
D.O.T. HAZARD CLASS: NONE
D.O.T. LABEL REQUIRED (49 CFR 172.101): NONE
D.O.T. PACKAGING GROUP: NONE
EPA WASTE CODE - IF DISCARDED (40 CFR 261): NONE

MANUFACTURER: DAP, INC.
P.O. BOX 277
DAYTON, OH 45401-0277

PHONE: 24 HOUR EMERGENCY:
INFO TRAC 1-800-535-5053
DAP, INC. 1-800-543-3840
GENERAL INFORMATION:
DAP, INC. 1-800-543-3840

SECTION II. INGREDIENTS AND HAZARDS

INGREDIENT NAME: PERCENT: EXPOSURE LIMITS:

INGREDIENTS ARE NOT REGULATED BY OSHA AND ARE CONSIDERED TRADE SECRETS.

INGREDIENTS PER NEW JERSEY RIGHT TO KNOW ACT: WATER 7732-18-5, HYDROUS ALUMINUM SILICATE 1335-30-4, TSRN-618608-5025P, TSRN-618608-5093P, LIMESTONE 1317-85-3, AND TSRN-618608-5037P.

MATERIAL SAFETY DATA SHEET

DAP CANADA INC.
475 FINCHdene SQUARE
UNIT 5
SCARBOROUGH, ONTARIO MIX 1B7

MSDS NO: DAP / 30807
INTERNAL ID: 30807
DAP WELDWOOD MULT-PURPOSE
FLOOR ADHESIVE
REVISION: 6
DATE: JANUARY 17, 1995

1 SECTION III. PHYSICAL DATA 1

APPEARANCE & ODOR: OFF WHITE PASTE.

MELTING POINT: 212F (H2O)
VAPOR PRESSURE: 17.5 MM HG @ 20C (H2O)
WATER SOLUBILITY (%): NE
VAPOR DENSITY (AIR=1): >1

EVAPORATION RATE: (N-BUTYL
ACETATE=1): <1
SPECIFIC GRAVITY (H2O=1): 1.3
% VOLATILE BY VOLUME: 50-55

VISCOSITY: 95,000 - 120,000 CENTIPOISE

VOC LESS WATER LESS EXEMPT SOLVENTS (G/LITER): 0 (CALCULATED)
VOC MATERIAL (G/LITER): 0 (CALCULATED)

1 SECTION IV. FIRE AND EXPLOSION DATA 1

FLASH POINT (METHOD): >200F (S.C.C.) LIMITS: LEL %: NE UEL %: NE

EXTINGUISHING MEDIA: FOAM, CARBON DIOXIDE, DRY CHEMICAL

UNUSUAL FIRE OR EXPLOSION HAZARDS: NONE KNOWN.

SPECIAL FIRE-FIGHTING PROCEDURES: USE WATER SPRAY TO COOL EXPOSED CONTAINER.

1 SECTION V. REACTIVITY DATA 1

MATERIAL IS STABLE. HAZARDOUS POLYMERIZATION WILL NOT OCCUR.

CHEMICAL INCOMPATIBILITIES: STRONG OXIDIZERS AND CAUSTICS

CONDITIONS TO AVOID: EXCESSIVE HEAT AND FREEZING.

HAZARDOUS DECOMPOSITION PRODUCTS: NORMAL COMBUSTION PRODUCTS, I.E. COX, NOX

1 SECTION VI. HEALTH HAZARD INFORMATION 1

THIS PRODUCT IS NOT CONSIDERED A CARCINOGEN BY IARC, NTP, OR OSHA.

MEDICAL CONDITIONS WHICH MAY BE AGGRAVATED BY CONTACT: NONE KNOWN

DAP CANADA INC.
475 FINCHdene SQUARE
UNIT 5
SCARBOROUGH, ONTARIO MIX 1B7

MSDS NO: DAP / 30807
INTERNAL ID: 30807
DAP WELdWOOD MULT-PURPOSE
FLOOR ADHESIVE
REVISION: 6
DATE: JANUARY 17, 1995

1 HEALTH HAZARD INFORMATION CONTINUED FROM PAGE 2 1

FIRST AID:

EYE CONTACT: FLUSH WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES.
CONTACT A PHYSICIAN IMMEDIATELY.

SKIN CONTACT: WASH IMMEDIATELY WITH SOAP AND WATER.

INHALATION: REMOVE TO FRESH AIR. CONTACT PHYSICIAN IMMEDIATELY.

INGESTION: DO NOT INDUCE VOMITING. CONTACT PHYSICIAN OR REGIONAL
POISON CONTROL CENTER IMMEDIATELY FOR ADDITIONAL
TREATMENT.

1 SECTION VII. SPILL, LEAK AND DISPOSAL PROCEDURES 1

SPILL / LEAK PROCEDURES: USE ABSORBENT MATERIAL OR SCRAPE UP DRIED MATERIAL AND
PLACE INTO CONTAINERS.

WASTE MANAGEMENT / DISPOSAL: DISPOSE OF ACCORDING TO FEDERAL, STATE AND LOCAL
STANDARDS. DO NOT REUSE EMPTY CONTAINERS. THIS PRODUCT DOES NOT MEET THE
DEFINITION OF A HAZARDOUS WASTE ACCORDING TO USEPA HAZARDOUS WASTE REGULATIONS (40
CFR SECTION 260).

1 SECTION VIII. SPECIAL PROTECTION INFORMATION 1

PERSONAL PROTECTIVE EQUIPMENT:

GOGGLES: SAFETY GLASSES WITH SIDE SHIELDS RECOMMENDED.

GLOVES: RECOMMENDED FOR REPEATED OR PROLONGED CONTACT WITH SKIN.

RESPIRATOR: NOT REQUIRED UNDER NORMAL USAGE AND WITH ADEQUATE VENTILATION.
SEE VENTILATION SECTION BELOW.

WORKPLACE CONSIDERATIONS:

VENTILATION: GOOD MECHANICAL VENTILATION AND LOCAL EXHAUST.

SAFETY STATIONS:
NOT REQUIRED.

CONTAMINATED EQUIPMENT:
WASH CONTAMINATED CLOTHING BEFORE REUSE.

MATERIAL SAFETY DATA SHEET

DAP CANADA INC.
475 FINCHDENE SQUARE
UNIT 5
SCARBOROUGH, ONTARIO MIX 1B7

MSDS NO: DAP / 30807
INTERNAL ID: 30807
DAP WELDWOOD MULT-PURPOSE
FLOOR ADHESIVE
REVISION: 6
DATE: JANUARY 17, 1995

SECTION IX. SPECIAL PRECAUTIONS

STORAGE SEGREGATION: STORE AWAY FROM CAUSTICS AND OXIDIZERS.

SPECIAL HANDLING / STORAGE: KEEP OUT OF REACH OF CHILDREN. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE. KEEP CONTAINERS FROM EXCESSIVE HEAT AND FREEZING. DO NOT STORE AT TEMPERATURES ABOVE 120F.

OTHER PRECAUTIONS: USE IN A WELL VENTILATED AREA. PROVIDE FRESH AIR SUCH THAT CHEMICAL ODORS CANNOT BE DETECTED DURING USE AND WHILE DRYING.

DOT CLASS: SEE SECTION I

UN REGISTER: SEE SECTION I

RECOMMENDED INDUSTRIAL HYGIENE AND SAFE HANDLING PROCEDURES ARE BELIEVED TO BE GENERALLY APPLICABLE. HOWEVER, EACH USER SHOULD REVIEW THE RECOMMENDATIONS IN SPECIFIC CONTEXT OF THE INTENDED USE AND DETERMINE IF THEY ARE APPROPRIATE.

END OF MSDS 30807

--- PAGE 4



DAP Inc.
P.O. Box 277
Dayton, OH 45401-0277
513/867-4481
Fax: 513/667-3331

To: JIM

Date: 8-16-95

From: JUDY KIMINAS

Page 1 of 5

ENCLOSED IS A DAP MATERIAL SAFETY DATA SHEET(S) THAT COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200.

IT IS DAP'S POLICY TO LIST AN INGREDIENT ON THE MSDS AND GIVE APPROPRIATE WARNINGS IF IT IS IN THE PRODUCT AT GREATER THAN 1% (OR 0.1% IF A CARCINOGEN) AND IT MEETS ANY ONE OF THE FOLLOWING CRITERIA:

- 1) IS LISTED IN THE OSHA Z-TABLES WITH AN ESTABLISHED PERMISSIBLE EXPOSURE LIMIT (PEL);
- 2) THE ACGIH HAS ESTABLISHED A THRESHOLD LIMIT VALUE (TLV OR 8-HOUR TIME WEIGHTED AVERAGE);
- 3) IS LISTED BY NTP, IARC OR OSHA AS A KNOWN CARCINOGEN;
- 4) HAS A FLASH POINT BELOW 200 DEGREES F.;
- 5) MAY UNDERGO HAZARDOUS POLYMERIZATION;
- 6) IS A STRONG OXIDIZING OR CAUSTIC AGENT;
- 7) IS LISTED ON THE SARA 313 LIST OF REPORTABLE CHEMICALS.

ABBREVIATIONS USED IN DAP'S MATERIAL SAFETY DATA SHEETS:

- ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS
IARC - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER
NA - NOT APPLICABLE
NE - NOT ESTABLISHED
PEL - PERMISSIBLE EXPOSURE LIMIT
NTP - NATIONAL TOXICOLOGY PROGRAM
SARA - SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT OF 1986
STEL - SHORT TERM EXPOSURE LIMIT
TLV - THRESHOLD LIMIT VALUE (8-HR TIME WEIGHTED AVERAGE OR TWA)
VOC - VOLATILE ORGANIC COMPOUND
NJRTK - NEW JERSEY RIGHT TO KNOW LAW

PLEASE FILE THIS INFORMATION WITH YOUR PERMANENT RECORDS OF PRODUCT INFORMATION.

PRIMARY ENTRY ROUTE(S): SKIN CONTACT AND INGESTION.

ACUTE EFFECTS: MAY IRRITATE EYES, SKIN, NOSE AND RESPIRATORY TRACT.

CHRONIC EFFECT(S): PROLONGED OR REPEATED CONTACT WITH SKIN MAY CAUSE IRRITATION.

HEALTH HAZARD INFORMATION CONTINUES ON PAGE 3

--- PAGE 2