



Revision Number: 003.0 Issue date: 03/20/2012

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: 569 Thread Sealant High Strength

Hydraulic Sealant

Product type: Anaerobic Sealant

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

IDH number: 135492

Item number:56931Region:United States

Contact information: Telephone: 860.571.5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

 Physical state:
 Liquid
 HEALTH:
 *2

 Color:
 Brown
 FLAMMABILITY:
 1

 Odor:
 Mild
 PHYSICAL HAZARD:
 1

Personal Protection: See MSDS Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: May cause respiratory tract irritation.

Skin contact: May cause allergic skin reaction. May cause skin irritation.

Eye contact: May cause irritation.

Ingestion: Not expected to be harmful by ingestion.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Polyglycol dimethacrylate	25852-47-5	30 - 60
Polyglycol dioctanoate	18268-70-7	10 - 30
Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	9011-53-4	10 - 30
Cumene hydroperoxide	80-15-9	1 - 5
Cumene	98-82-8	0.1 - 1

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention.

IDH number: 135492 Product name: 569 Thread Sealant High Strength Hydraulic Sealant Page 1 of 5

Skin contact: Wash with soap and water. Remove contaminated clothing and footwear.

Wash clothing before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Flush with copious amounts of water, preferably, lukewarm water for at least

15 minutes, holding eyelids open all the time. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Autoignition temperature: Not available. Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available.

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: None

IDH number: 135492

Hazardous combustion products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic

vapours.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Soak up with inert absorbent material (e.g. sand, silica gel, acid binder,

universal binder, sawdust). Store in a partly filled, closed container until

disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation.

Storage: For safe storage, store at or below 38 °C (100.4 °F)

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

For information on product shelf life contact Henkel Canada Customer Service at (905) 814-6511.

EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Polyglycol dimethacrylate	None	None	None	None
Polyglycol dioctanoate	None	None	None	None
Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	None	None	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Cumene	50 ppm TWA	50 ppm (245 mg/m3) TWA (SKIN)	None	None

Engineering controls: No specific ventilation requirements noted, but forced ventilation may still be

required if concentrations exceed occupational exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

mit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Use impermeable gloves and protective clothing as necessary to prevent skin

contact. Neoprene gloves. Butyl rubber gloves. Natural rubber gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid
Color: Brown
Odor: Mild

Odor threshold: Not available. pH: Not applicable

 Vapor pressure:
 < 5 mm hg (27 °C (80.6 °F))</td>

 Boiling point/range:
 > 149 °C (> 300.2 °F)

Melting point/ range:Not available.Specific gravity:1.049Vapor density:Not available.

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:
Plammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partition acceptable limits - lower:
Not available.
Not available.
Solubility in water:
Solubility in water:
Not available.

Partition coefficient (n-octanol/water): Not available.

VOC content: 0.81 %; 7.74 g/l

10. STABILITY AND REACTIVITY

Stability: Stable

IDH number: 135492

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of sulfur. Oxides of nitrogen. Irritating organic

vapours.

Incompatible materials: Strong oxidizing agents.

Conditions to avoid: See "Handling and Storage" (Section 7) and "Incompatibility" (Section 10).

11. TOXICOLOGICAL INFORMATION

Acute oral product toxicity: LD50 (rat) > 5,000 mg/kg (Estimated)

Acute dermal product toxicity: LD50 (rabbit) > 2,000 mg/kg (Estimated)

Product name: 569 Thread Sealant High Strength Hydraulic Sealant

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Polyglycol dimethacrylate	No	No	No
Polyglycol dioctanoate	No	No	No
Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	No	No	No
Cumene hydroperoxide	No	No	No
Cumene	No	Group 2B	No

Hazardous components	Health Effects/Target Organs
Polyglycol dimethacrylate	Irritant, Allergen
Polyglycol dioctanoate	Irritant
Methacrylic acid, isobutyl ester, polymer with butyl methacrylate	Irritant
Cumene hydroperoxide	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Cumene	Central nervous system, Irritant, Lung

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

Not regulated
None
None
None

15. REGULATORY INFORMATION

United States Regulatory Information

IDH number: 135492

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

Product name: 569 Thread Sealant High Strength Hydraulic Sealant Page 4 of 5

CERCLA/SARA 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cumene hydroperoxide (CAS# 80-15-9).

California Proposition 65: This product contains a chemical known in the State of California to cause cancer.

Canada Regulatory Information

IDH number: 135492

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New information added in Section(s): 1, 3, 8, 11, 14, 15

Prepared by: Kyra Kozak Woods, Manager, Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.