

SAFETY DATA SHEET SKASOL 359-SP

Section 1: Identification

Product Identifier: SKASOL 359-SP

Recommended Use: Boiler Scale and Corrosion Inhibitor

Manufacturer's Name and Address: SKASOL Incorporated

1696 West Grand Avenue Oakland, CA 94607-1607

Manufacturer's Telephone: (510) 839-1000

24 Hour Emergency Telephone (800) 424-9390

Section 2: Hazard(s) Identification

Hazard Classification: Corrosive

Signal Word: Warning

GHS Hazard Phrase(s): H301: Toxic if swallowed

H311: Toxic in contact with skin H318: Causes serious eye damage H333: May be harmful if inhaled

GHS Precaution Phrase(s): P262: Do not get in eyes, on skin, or on clothing

P264: Wash...thoroughly after handling

P270: Do not eat, drink or smoke when using this product P281: Use personal protective equipment as required

NFPA Rating

| HEALTH | 2 |
|------------|---|
| FIRE | 0 |
| REACTIVITY | 0 |

Section 3: Composition/Information on Ingredients

| Chemical Name | CAS Number | Percent | Limits in Air ACGIH TLV | (give units) OSHA PEL | Other (specify) |
|--------------------------|------------|---------|----------------------------|-----------------------|-----------------|
| Sodium Hydroxide | 1310-73-2 | <5% | 2mg/mg ³ | 2mg/mg ³ | ceiling |
| 2-(Diethylamino) Ethanol | 100-37-8 | <5% | 10 ppm | | _ |
| Proprietary Ingredients | | >90% | | | |
| Total | | 100% | | | |

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.



Section 4: First-aid Measures

Eye Contact Immediately flush with plenty of water, raising eyelids often to help irrigation and continue

for at least 15 minutes. Get medical assistance.

Skin Contact Flush with plenty of water. Remove contaminated clothing. If skin is slippery, alkalinity is

still present. Continue flushing until slipperiness is gone.

Inhaled Remove to fresh air. If not breathing give artificial respiration (preferably mouth to mouth).

Call a physician or poison control center.

Swallowed If conscious drink large quantities of water or milk. Do not induce vomiting. Get medical

attention. Never give anything by mouth to an unconscious person.

Section 5: Fire-fighting Measures

Fire extinguishing materials:

| Water | Х | Foam | Х | CO ₂ | Х | Dry | Х | Other | |
|-------|---|------|---|-----------------|---|----------|---|-------|--|
| | | | | | | Chemical | | | |

Special fire fighting procedures: Wear full protective clothing and respiratory protection.

Unusual fire and explosion hazards: None.

Section 6: Accidental Release Measures

Spill response procedures: Dike area to contain the spill. Small spills may be flushed and diluted

with lots of water and washed to a sewer connected to a waste

treatment plant.

Preparing wastes for disposal: Larger spills should be contained and washed with plenty of water to a

sewer connected to a waste treatment plant. Any DOT container is

suitable for temporarily holding neutralized waste.

Section 7: Handling and Storage

Precautions to be taken in handling: Avoid contact. Do not eat or drink near container.

When not in use, drums should be tightly sealed.

Keep drum from freezing.

Avoid storing plastic containers outside in direct sunlight. Prolonged storage in direct sunlight may compromise the quality of the container.



Section 8: Exposure Controls / Personal Protection

Ventilation and Engineering

Controls:

Local exhaust ventilation should be sufficient to minimize employee exposure

to mist below OSHA PEL

Respiratory Protection: When conditions require it, use a respirator approved by NIOSH/MSHA with a

dust/mist filter. Respiratory protection programs must meet or exceed the

requirements of Title 29 CFR 1910.134

Eye Protection: Safety glasses or chemical safety goggles.

Gloves: Nitrile, neoprene or natural rubber.

1115

Other Clothing and equipment Rubber boots with safety toes, rubber aprons, plastic hard hats should be

used when necessary to prevent skin contact.

Work practices, hygienic

practices:

Protective clothing and use of equipment must be in accordance with Title 29

CFR Sections 1910.132 and 1910.133

Other Handling and Storage

Needs:

Provide emergency eye wash stations and emergency shower facilities near

use and handling areas.

Measures during Maintenance: Chemical feed pumps should be routinely washed out with water. Plastic

tubing and fittings should be frequently inspected for leaks and clogs. As with all automatic equipment, be certain that the power is disconnected before

performing any adjustments or repairs. Use all above precautions.

Section 9: Physical and Chemical Properties

| Appearance | Clear liquid | Upper/lower flammability limits | None |
|----------------------------|----------------|---------------------------------|---------------|
| Odor | Organic odor | Vapor pressure | Not available |
| Odor threshold | Not available | Vapor Density | Not available |
| рН | 12.5 - 13.9 | Relative density | 1.09 - 1.21 |
| Melting Point or Range | Not applicable | Solubility in Water | Complete |
| Boiling Point or Range, °F | 218 | Auto ignition temperature, °F | None |
| Flash point, °F | none | Viscosity | Not Available |
| Evaporation Rate | Not available | Flammability | None |



Section 10: Stability and Reactivity

| Stability | X Stable | Unstable | | | | |
|---|-------------------------------|--------------------------------------|--|--|--|--|
| Hazardous polymerization: | May occur | X Will not occur | | | | |
| Conditions to avoid: | | Do not mix with strong acids. | | | | |
| Incompatibility (materials to avoid |)): | Strong acids. | | | | |
| Hazardous decomposition products: | | Oxides of sulfur, heat. | | | | |
| Section 11: Toxicological Information | | | | | | |
| Toxicitiy Studies: | No toxicity studies | have been conducted on this product. | | | | |
| Acute: | May cause burns v | vith acute exposure. | | | | |
| Chronic: | Same as acute, bu | it with milder symptoms. | | | | |
| Acute oral toxicity Acute inhalation toxicity Acute dermal toxicity | Unknown Unknown Unknown | | | | | |

Section 12: Ecological Information

Avoid release into the environment - harmful to aquatic organisms.

Section 13: Disposal Considerations

Waste Disposal Method: Dispose in accordance with local, state, and federal regulations.



Section 14: Transport Information

UN Number: UN1760

UN Proper Shipping Name: Corrosive liquids, N.O.S.,

(contains Sodium Hydroxide, 2-(Diethylamino) Ethanol)

Transport Hazard Class(es) 8

Packing Group II

Section 15: Other Regulatory Information

Unknown

Section 16: Other Information

Date prepared or revised: May 31, 2015

Name of preparer: Brian Ford

DISCLAIMER: This information is believed to be accurate and represents the best information currently available to us. However, we make no warranty or merchantability or any other warranty, expressed or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes.