

FROM 314 942 3663

2.23.1994 14:02

P. 6

**KILY AEROSOL**  
61658-10064-4  
AEROSOL GEFRAY PRIMER (60% VOC)

A02/036

**SECTION V - HEALTH HAZARD DATA**

**EFFECTS OF OVEREXPOSURE:** Inhalation: Anesthetic, Irritation of the respiratory tract or acute nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness, or coma. Skin or eye contact: Primary irritant.

**MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE:** Reports have associated repeated and prolonged occupation overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

**PRIMARY ROUTE(S) OF ENTRY:**

DERMAL <input checked="" type="checkbox"/>	INHALATION <input checked="" type="checkbox"/>	INGESTION <input type="checkbox"/>
--	--	------------------------------------

**EMERGENCY AND FIRST AID PROCEDURES:** Inhalation: Remove to fresh air. Restore breathing. Treat symptomatically. Consult a physician.  Splash (eyes): Flush immediately with large amounts of water for at least 15 minutes. Take to physician for medical treatment.  Splash (skin): Wash affected areas with soap and water. Remove contaminated clothing. Consult a physician if irritation persists. Ingestion: Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult physician or poison control center immediately. Treat symptomatically.

**SECTION VI - REACTIVITY DATA**

**STABILITY:** UNSTABLE  STABLE

**HAZARDOUS POLYMERIZATION:** MAY OCCUR  WILL NOT OCCUR

**HAZARDOUS DECOMPOSITION PRODUCTS:** May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain: carbon monoxide, carbon dioxide, hydrocarbons, oxides of nitrogen and other products of combustion.

**CONDITIONS TO AVOID:** High temperatures or high humidities. Heat, sparks or open flame.

**INCOMPATIBILITY: (MATERIALS TO AVOID)** Peroxides or strong oxidizing agents.

**SECTION VII - SPILL OR LEAK PROCEDURES**

**STEPS TO BE TAKEN IN CASE MATERIALS RELEASED OR SPILLED:** Limit spread of spill or leak. Remove all sources of ignition. Soak up with inert absorbent material. Use non-sparking tools when removing wet absorbent. See Section VIII for required protective measures. Keep material out of sewers and/or drains.

**WASTE DISPOSAL METHOD:** Dispose of in accordance with all local, state and federal regulations. Empty primer and empty aerosol containers may be landfilled. Full or partially full aerosol containers should not be punctured or incinerated and should be treated as hazardous waste which requires disposal at an approved hazardous waste site.

**SECTION VIII - SAFE HANDLING AND USE INFORMATION**

**RESPIRATORY PROTECTION:** If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 230 or equivalent) or leave the area.

**VENTILATION:** Ventilation of sufficient volume and pattern should be provided to keep air contaminant concentrations below occupational exposure limits as shown in Section IIA.

**PROTECTIVE GLOVES:** Required, rubber or neoprene to prevent skin contact.

**EYE PROTECTION:** Use safety eyewear including splash guards or side shields.

**OTHER PROTECTIVE EQUIPMENT:** Wear protective clothing. Remove and wash contaminated clothing before re-use.

**HYGIENIC PRACTICES:** Wash hands before eating or using the washroom. Smoke in smoking areas only.

**SECTION IX - SPECIAL PRECAUTIONS**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Store away from extreme heat, fire, or open flame. Store in accordance with OSHA 1910.106. Store in well ventilated areas. Store as level 3 aerosol (NFPA 30B).

**OTHER PRECAUTIONS: DO NOT TAKE INTERNALLY.** Avoid prolonged contact with skin. Keep closure tight and container upright to prevent leakage. Do not store near heat, sparks, or open flame. Drums of this material should be grounded and bonded when pouring. Containers must not be washed out or used for other purposes. Avoid contact with or breathing of vapors released during curing process. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

**DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES**

The information contained herein is based on data considered accurate. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. The product is no more hazardous than its component parts pursuant to 29CFR 1910.1205 (D). The technical information on this MSDS sheet is based upon information submitted by manufacturers and additional information furnished by distributor's chemical suppliers and manufacturers. Vendor assumes no responsibility for injury to vendor or third persons proximately caused by the material if reasonable safety procedures are not followed as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendor or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendor assumes the risk in his use of the material.

PREPARED BY: <i>William R. Banton</i>	DATE PREPARED: March 1, 1993
NAME AND TITLE: W.R. Banton, MSDS Coordinator	SUPERSEDES: August 27, 1990