


PLEDGE ELECTRONICS CLEANING & DUSTING SPRAY

National Fire Protection Association (NFPA)	Health		Reactivity	Hazardous Material Information System (HMIS)	Health	0
	Fire Hazard			4	Reactivity	0

Protective Clothing	None required.	Emergency Overview	Clear Aerosol. See Section 9. CAUTION: CONTENTS UNDER PRESSURE.
---------------------	----------------	--------------------	--

Section 1. Chemical Product and Company Identification

Product Name	PLEDGE ELECTRONICS CLEANING & DUSTING SPRAY	Code	94323
Product Use	Industrial/Institutional: Cleaning product.	PMS#	436676
MSDS#	126499002	Validation Date	5/28/2002
U.S. Headquarters Drackett Professional A Division of S.C. Johnson Commercial Markets, Inc. 8310 16th Street Sturtevant, Wisconsin 53177-0902 Phone: (888) 352-2249	Print Date	5/28/2002	
	Supersedes	5/28/2002.	
	In Case of Emergency	(800) 851-7145	

Section 2. Composition and Information on Ingredients

Ingredients	CAS #	% by Weight	Exposure Limits	LC50/LD50
Ammonium Hydroxide	1336-21-6	<0.5	Not available.	ORAL (LD50): Acute: 350 mg/kg [Rat].
2-Butoxyethanol	111-76-2	1-5	TWA: 120 (mg/m ³) from OSHA (PEL) [United States] TWA: 97 (mg/m ³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 506 mg/kg [Rat]. DERMAL (LD50): Acute: 406 mg/kg [Rabbit]. VAPOR (LC50): Acute: 450 ppm 4 hours [Rat].
Isobutane	75-28-5	3-7	Not available.	VAPOR (LC50): Acute: 0.0057 ppm 0.25 hours [Rat].
Isopropyl Alcohol	67-63-0	10-30	TWA: 980 STEL: 1225 (mg/m ³) from OSHA (PEL) [United States] TWA: 983 STEL: 1230 (mg/m ³) from ACGIH (TLV) [United States]	ORAL (LD50): Acute: 5045 mg/kg [Rat]. DERMAL (LD50): Acute: 12800 mg/kg [Rabbit]. VAPOR (LC50): Acute: 16000 ppm 8 hours [Rat].
Water	7732-18-5	60-100	Not available.	Not available.

Section 3. Hazards Identification

Routes of Entry	Inhalation. Eye contact.
Potential Acute Health Effects	
<i>Eyes</i>	None known.
<i>Skin</i>	None known.
<i>Inhalation</i>	None known.
<i>Ingestion</i>	None known.
Medical Conditions Aggravated by Overexposure:	None known.
See Toxicological Information (section 11)	

PLEDGE ELECTRONICS CLEANING & DUSTING SPRAY

Section 4. First Aid Measures

Eye Contact	Rinse with plenty of running water.
Skin Contact	Rinse with plenty of running water.
Inhalation	No specific first aid measures are required.
Ingestion	No specific first aid measures are required.

Section 5. Fire Fighting Measures

Flammability of the Product	NFPA 30B Level 1 Aerosol.
Flash Points	< 7°C (propellant).
Products of Combustion	None known.
Fire Fighting Media and Instructions	Use water spray to keep fire-exposed containers cool. Dry chemical, carbon dioxide. Fight fire from protected location or maximum possible distance. In case of fire and/or explosion do not breathe fumes.
Protective Clothing (Fire)	Put on appropriate personal protective equipment (see Section 8.).
Special Remarks on Fire and Explosion Hazards	Aerosol product - Containers may rocket or explode in heat of fire.

Section 6. Accidental Release Measures

Personal Precautions	Put on appropriate personal protective equipment (see Section 8.).
Environmental Precautions and Clean-up Methods	Eliminate all ignition sources. In the event of major spillage: Use appropriate containment to avoid environmental contamination. Take up with sand or other non-combustible material. Place in suitable clean, dry containers for disposal by approved methods.

Section 7. Handling and Storage

Handling	Do not puncture or incinerate. FOR INDUSTRIAL USE ONLY
Storage	Store in a dry, cool and well-ventilated area. Protect from freezing. Keep away from heat, sparks and flame. Do not puncture or incinerate. Pressurized container: protect from sunlight and do not expose to temperature exceeding 120°F (50°C). Do not pierce or burn, even after use. KEEP OUT OF REACH OF CHILDREN.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	No special ventilation requirements. General room ventilation is adequate.
Personal Protection	
<i>Eyes</i>	No special requirements under normal use conditions.
<i>Hands</i>	No special requirements under normal use conditions.
<i>Respiratory</i>	No special requirements under normal use conditions.
<i>Feet</i>	No special requirements under normal use conditions.
<i>Body</i>	No special protective clothing is required.

Section 9. Physical and Chemical Properties

Physical State and Appearance	Liquid. (Aerosol.)
Odor	Fresh.
Color	Clear
pH	10.7 [Basic.]
Specific Gravity	0.95
Boiling/Condensation Point	100°C (212°F)
Melting/Freezing Point	0°C (32°F)
Solubility in water	Complete.

PLEDGE ELECTRONICS CLEANING & DUSTING SPRAY

Section 10. Stability and Reactivity

Stability and Reactivity	The product is stable.
Conditions of Instability	Excessive heat.
Incompatibility with Various Substances	Not available.
Hazardous Decomposition Products	When exposed to fire: Produces normal products of combustion.
Hazardous Polymerization	Will not occur.

Section 11. Toxicological Information

Acute toxicity	ORAL (LD50) Estimated to be greater than 5000 mg/kg (rat). DERMAL (LD50) Estimated to be greater than 2000 mg/kg (rat).
Effects of Chronic Exposure	None known.
Other Toxic Effects	Not available.

Section 12. Ecological Information

Not available.

Section 13. Disposal Considerations

Waste Information	If possible, recycle empty aerosol cans to the nearest steel recycling center. Use up package or give to someone who can. Dispose of according to all federal, state and local regulations.
--------------------------	---

Section 14. Transport Information

DOT Classification	
DOT Proper Shipping Name	Please refer to the Bill of Lading/receiving documents for up to date shipping information.
TDG Classification	
TDG Class	Not applicable.

Section 15. Regulatory Information**Reporting in this section is based on ingredients disclosed in Section 2****US Regulations**

Federal SARA 313 toxic chemical notification and release reporting: Isopropyl Alcohol
Clean air act (CAA) 112 regulated flammable substances: Isobutane
CERCLA: Hazardous substances.: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane

State New Jersey spill list: Isopropyl Alcohol, 2-Butoxyethanol
New Jersey: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane
Massachusetts spill list: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane
Massachusetts RTK: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane
Pennsylvania RTK: Isopropyl Alcohol, 2-Butoxyethanol, Isobutane

This product is not subject to the reporting requirements under California's Proposition 65.

Registered Product Information Not applicable.

Canadian Regulations

Canadian NPRI Not applicable.

WHMIS Classification Not applicable.

WHMIS Icon

Registered Product Information Not applicable.

Chemical Inventory Status All ingredients of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

PLEDGE ELECTRONICS CLEANING & DUSTING SPRAY

Section 16. Other Information

Other Special Considerations	MSDS Serial Range: 001-002.
------------------------------	-----------------------------

Version	1.01
---------	------

Notice to Reader

This document has been prepared using data from sources considered technically reliable. It does not constitute a warranty, express or implied, as to the accuracy of the information contained within. Actual conditions of use and handling are beyond seller's control. User is responsible to evaluate all available information when using product for any particular use and to comply with all Federal, State, Provincial and Local laws and regulations.

Product name: PLEDGE ELECTRONICS

Product code: 126499002

Date: 2006-11-02

SARA 313 ADDENDUM TO MSDS

This product contains the chemicals listed below which are subject to the reporting requirements of Section 313 of the EPCRA/SARA regulations in the United States.

Ingredient(s)	CAS #	Weight %
Isopropyl alcohol	67-63-0	13.775
2-butoxyethanol	111-76-2	2.85