# Safety Data Sheet



# according to OSHA Hazard Communication 29 CFR Part 1910.1200

## Section 1. Identification

Product Information: 22R-A007

Product Name: RED REGULAR DRY WATERBORNE TRAFFIC MARKING PAINT

Recommended Use: Liquid Paint

Application Method: Liquid Paint

Supplied by: Aexcel Corporation

7373 Production Drive. Mentor, OH 44060

Emergency Telephone: Chemtrec: 800-424-9300
Safety Data Sheet Coordinator: IWebb@AexcelCorp.com

# Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Flammable liquid and vapor. Skin and eye irritant.

**GHS Classification** 

No GHS Classifications were found

Symbol(s) of Product

No GHS Symbols Exist

Signal Word

No Signal Word has been assigned

# Section 3. Composition/Information on ingredients

 Chemical Name
 CAS-No.
 Wt. %
 GHS Symbols
 GHS Statements

 ETHYLENE GLYCOL
 107-21-1
 1.0-2.5
 GHS07-GHS08
 H302-320-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air. Oxygen or artificial respiration if needed.

FIRST AID - SKIN CONTACT: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

FIRST AID - EYE CONTACT: Flush eye(s) immediately with plenty of water.

FIRST AID - INGESTION: Consult a physician. If a person vomits when lying on his back, place him in the recovery position.

# Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Water Fog

## Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

# Section 7. Handling and storage





**HANDLING:** Containers of this material may be hazardous when emptied. All metal parts of the mixing and processing equipment must be grounded. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material. Do not reuse empty containers. Keep away from food and drink. Keep away from open flames, hot surfaces and sources of ignition.

STORAGE: Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up.

# Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

Chemical NameACGIH TLV-TWAACGIH-TLV STELOSHA PEL-TWAOSHA PEL-CEILINGETHYLENE GLYCOL100NE50N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

#### **Personal Protection**



**RESPIRATORY PROTECTION:** In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Impervious clothing.



**HYGIENIC PRACTICES:** General industrial hygiene practice.

# 9. Physical and Chemical Properties

193 - 482 Vapor Density: 2.2 **Boiling Range:** Odor Threshold: Odor: Characteristic NE **Evaporation Rate:** Appearance: Heavy Red Liquid <1.0 Specific Gravity: Solubility in Water: NE 1.315 pH: Freeze Point: NΕ NE Viscosity: Vapor Pressure: <.10 NE Flash Point, °F >200 **Physical State:** Liquid

(See section 16 for abbreviation legend)

<u>CHEMICAL NAME</u> <u>VAPOR DENSITY</u> <u>EVAPORATION RATE</u> <u>BOILING POINT</u> <u>VP mmHg</u> <u>at DEG. F</u>

ETHYLENE GLYCOL 2.2 < 1.0 379 < .10 68

# Section 10. Stability and reactivity

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Avoid contact with skin, eyes and clothing. **INCOMPATIBILITY:** Incompatible with strong acids and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition if stored and applied as directed.

# Section 11. Toxicological information



## **Practical Experiences**

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause intense irritation to the respiratory tract (nose, mouth, mucous membranes). Prolonged, repeated, or high exposures may cause weakness and depression of the central nervous system. In extreme cases, drowsiness and possibly loss of consciousness may occur.

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Direct skin contact may cause moderate to severe irritation and possibly dermatitis. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Mist and vapors may cause eye irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Ingestion of larger amounts may cause defects to the central nervous system (e.g. dizziness, headache). May cause cyanosis.

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u> Name according to EEC Oral LD50 Dermal LD50 Vapor LC50

107-21-1 ETHYLENE GLYCOL N.I. N.I. N.I. N.I.

N.I. - No Information

# Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

# Section 13. Disposal considerations



#### **Product**

**DISPOSAL METHOD:** Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

## Section 14. Transport information

#### SPECIAL TRANSPORT PRECAUTIONS: No Information

**DOT Proper Shipping BOT Technical Name:**Paint, Latex
Paint

**DOT Hazard Class:** Non-Hazardous **DOT UN/NA Number:** Non-Regulated

# Section 15. Regulatory information

# U.S. Federal Regulations:

## **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

## **SARA SECTION 312:**

Chemical NameCAS-No.ETHYLENE GLYCOL107-21-1

#### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.ETHYLENE GLYCOL107-21-1VINYL ACETATE108-05-4

#### TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

## **U.S. State Regulations:**

#### **NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

 Chemical Name
 CAS-No.

 WATER
 7732-18-5

 LIMESTONE
 1317-65-3

VINYL-ACRYLIC EMULSION

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

 Chemical Name
 CAS-No.

 WATER
 7732-18-5

 LIMESTONE
 1317-65-3

VINYL-ACRYLIC EMULSION

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

Warning: The following ingredients present in the product are known to the state of California to cause Cancer:

No Proposition 65 Carcinogens exist in this product.

#### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

Warning: The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product.

## International Regulations: As follows -

### **CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

## Section 16. Other information, including date of preparation of the last revision

Revision Date: 10/21/2015 Supercedes Date: New MSDS

Reason for revision: GHS

Datasheet produced by: Regulatory Department

**HMIS Ratings:** 

Health:	1	Flammability:	0	Reactivity:	0	Personal Protection:	X

Volatile Organic Compounds, gr/ltr: 76

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302 Harmful if swallowed. H320 Causes eye irritation

H373 May cause damage to organs through prolonged or repeated exposure.

## Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS07



GHS08

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information